

## TALKATOR NG Model „SPC“

**TALKATOR** and **TALK-O-MAT** were the first two own machine lines of the company ROLF SCHLICHT GmbH in the 60s to 80s. They are the reason for the worldwide success of the machines. Based on the simplicity of these old machines we have developed two new attractive products which are used in different areas.

The **TALKATOR NG "SPC"** for dust-free powdering of cables, hoses, wires and profiles in slow running production processes as well as the **TALKATOR NG "DR"** for small parts / granules powdering.

The **TALKATOR "SPC"** series for cables, hoses, wires and profiles is settled below the RSC NG line and shows its strength in slow running, simple cable production as well as in the production of strands and profiles in the extrusion sequence in the rubber industry. Especially in the rubber industry the **TALKATOR** has significant cost advantages, as the processes run at low speeds. This is made possible by the application of **RS AirStreamTechnology®**, which avoids expensive brush solutions in most applications, but still provides very good coating results.

The powdering is done by 1-2 **AST** powder guns connected to up to two jet pumps. The new, patented coating technology **RS AirStreamTechnology®** is able to achieve a very fine and even coating on the product at production speeds of up to 100 m/min, even without electrostatics.

For further technical data and options please refer to the chart "Technical data of the TALKATOR".



## WORD NOVELTY

- ✓ Powdering of cables, hoses, wires and profiles in very slow processes
- ✓ Completely newly developed machine, consistently simple
- ✓ **RS AirStreamTechnology®**
- ✓ Dosed coating without e-statics
- ✓ Absolutely dust-free operation
- ✓ "Easy Change" filter system
- ✓ Optionally "Quick Bag" filling system
- ✓ Optionally mobility package
- ✓ Optionally compressed air dryer

**POWDERING IN RUBBER & CABLE INDUSTRY**  
with high precision...

# TECHNICAL DATA

## TALKATOR NG Model „SPC“

Dust-free powdering of cables, hoses, profiles and bands in slow running production processes.

|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| Model:          | TALKATOR NG SPC                                                     |
| Diameter range: | up to max. Ø80 mm                                                   |
| Speeds:         | up to max. 100 m/min.                                               |
| Pistols:        | 1 - 2 <b>AST</b> -powder pistol ( <b>RS AirStream Technology®</b> ) |
| Compressed air: | 6 bar                                                               |
| Filling volume: | approx. 18 l                                                        |
| Supply voltage: | Country-specific                                                    |
| Dimensions:     | Depth: 1.110 mm (with filling), Width: 700 mm, Height: 1.745 mm     |

*Subject to technical modifications.*



### LOCATION REINFELD



### MANUFACTURING LOCATION



ROLF SCHLICHT GmbH  
Technologie für die Gummi-,  
Kunststoff- und Kabelindustrie  
Grootkoppel 16 • 23858 Reinfeld  
Germany  
Tel. +49 4533 6063-100  
e-mail: [info@schlicht-gmbh.de](mailto:info@schlicht-gmbh.de)  
internet: [www.schlicht-gmbh.de](http://www.schlicht-gmbh.de)

Your Distributor